



3 Type

- E** with threaded blind bore
- C** with plain blind bore, Tol. H7

d_1	2				d_3 H7 GN 6335.1 GN 6335.2 Type C Bushing steel	d_4	h_1	h_2	h_3	t min.	
	GN 6335.1 Type E Bushing steel	GN 6335.2 Type E Bushing steel	Bushing St. Steel								
32	M 6	M 6	-	M 6	B 6	-	12	20	10	9	12
40	M 6	M 6	M 8	M 8	B 6	B 8	14	25	13	10	14
50	M 8	M 8	M 10	M 10	B 8	B 10	18	32	20	12	18
63	M 10	M 10	M 12	M 12	B 10	B 12	20	40	25	14	22
80	M 12	M 12	M 16	M 16	B 16	-	25	50	30	17	30

Specification

- **GN 6335.1**
Plastic
Duroplast (PF)
black, shiny finish
Bushing
Steel zinc-plated, blue passivated —
- **GN 6335.2**
Plastic
Technopolymer (Polyamide PA)
- shock-resistant
- black, matt finish
Bushing
- Steel zinc-plated, blue passivated —
- Stainless Steel AISI 303 **NI**
- *ISO-Fundamental Tolerances* → Page XYZ
- *Plastic characteristics* → Page XYZ
- **RoHS compliant**



Information

Hand knobs GN 6335.1 / GN 6335.2 with protruding steel bushing have important advantages:

The face of the bushings exactly square to the bore and is with the complete diameter out of steel or Stainless Steel. The protruding steel bushing allows a perfect cross-dowels connection.

How to order (Duroplast, bushing steel)	1 d_1
1 2 3 GN 6335.1-50-B10-C	2 d_3 (d_2)
	3 Type

How to order (Technopolymer, bushing St. Steel)	1 d_1
1 2 3 4 GN 6335.2-63-M12-E-NI	2 d_2 (d_3)
	3 Type
	4 Material bushing