



- 1 Type**
- ST** Plastic (KT)
Technopolymer (Polyamide PA)
 - SK** Plastic (KU)
Duroplast (PF)

| d ₁ | d ₂ | Length l ≈ GN 6335.4 | | | | | | | | | | | | Length l ≈ GN 6335.5 | | | | | d ₃ | h ₁ | h ₂ |
|----------------|----------------|----------------------|----|----|----|----|----|---------|----|----|----|----|----|----------------------|----|----|----|----|----------------|----------------|----------------|
| | | Type ST | | | | | | Type SK | | | | | | Type ST | | | | | | | |
| 32 | M 6 | 16 | 20 | 25 | 30 | 35 | 45 | 16 | 20 | 25 | 30 | 35 | 45 | 10 | 16 | 20 | 25 | 30 | 14 | 20 | 10 |
| 40 | M 8 | 16 | 20 | 25 | 30 | 40 | 55 | 15 | 20 | 25 | 30 | 40 | 55 | 20 | 25 | 30 | 40 | - | 18 | 25 | 13 |
| 50 | M 10 | 25 | 30 | 35 | 45 | 55 | - | 25 | 30 | 35 | 45 | 55 | - | 20 | 25 | 30 | 45 | 55 | 22 | 32 | 20 |
| 63 | M 12 | 30 | 35 | 40 | 50 | 60 | - | 30 | 35 | 40 | 50 | 60 | - | 30 | 40 | 50 | - | - | 26 | 40 | 25 |
| 80 | M 16 | - | - | - | - | - | - | 30 | 40 | 50 | 60 | 70 | - | - | - | - | - | - | 35 | 50 | 30 |

Specification

- **GN 6335.4**
 - Threaded stud
Steel
zinc plated, blue passivated
 - Knob (Type ST)
Technopolymer (Polyamide PA)
shock-resistant
black matte
 - Knob (Type SK)
Duroplast
black shiny

- **GN 6335.5**
 - Threaded stud
Stainless Steel
M6... M10: AISI 304 Cu
M12: AISI 303
 - Knob (Type ST)
Technopolymer (Polyamide PA)
shock-resistant
black matte

- Plastic characteristics → Page XYZ
- Stainless Steel characteristics → Page XYZ
- RoHS compliant

Information

Hand knobs GN 6335.4 / GN 6335.5 comply with DIN 6335 type L.

see also...

- Hand knobs GN 6335.4 with loss protection GN 111.7 → Page XYZ
- Hand knobs GN 6335.5 with loss protection GN 111.7 → Page XYZ

How to order (Threaded stud steel)

GN6335.4-SK-80-M16-50

- 1 Type
- 2 d₁
- 3 d₂
- 4 Length l

How to order (Threaded stud Stainless Steel)

GN6335.5-ST-50-M10-25

- 1 Type
- 2 d₁
- 3 d₂
- 4 Length l