



- 1 Type**
- ST** Plastic (KT)
Technopolymer (Polyamide PA)
 - SK** Plastic (KU)
Duroplast (PF)

d ₁	d ₂	Length l ≈ GN 6335.4												Length l ≈ GN 6335.5						d ₃	h ₁	h ₂
		Type ST						Type SK						Type ST								
32	M 6	16	20	25	30	35	45	16	20	25	30	35	45	10	16	20	25	30	14	20	10	
40	M 8	16	20	25	30	40	55	15	20	25	30	40	55	20	25	30	40	-	18	25	13	
50	M 10	25	30	35	45	55	-	25	30	35	45	55	-	20	25	30	45	55	22	32	20	
63	M 12	30	35	40	50	60	-	30	35	40	50	60	-	30	40	50	-	-	26	40	25	
80	M 16	-	-	-	-	-	-	30	40	50	60	70	-	-	-	-	-	-	35	50	30	

Specification

- **GN 6335.4**
 - Threaded stud
Steel
zinc plated, blue passivated
 - Knob (Type ST)
Technopolymer (Polyamide PA)
shock-resistant
black matte
 - Knob (Type SK)
Duroplast
black shiny

- **GN 6335.5**
 - Threaded stud
Stainless Steel
M6... M10: AISI 304 Cu
M12: AISI 303
 - Knob (Type ST)
Technopolymer (Polyamide PA)
shock-resistant
black matte

- *Plastic characteristics* → Page 1483
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Information

Hand knobs GN 6335.4 / GN 6335.5 comply with DIN 6335 type L.

see also...

- *Hand knobs GN 6335.4 with loss protection GN 111.7* → Page 1426
- *Hand knobs GN 6335.5 with loss protection GN 111.7* → Page 1426

How to order (Threaded stud steel)

GN6335.4-SK-80-M16-50

- 1 Type**
- 2 d₁**
- 3 d₂**
- 4 Length l**

How to order (Threaded stud Stainless Steel)

GN6335.5-ST-50-M10-25

- 1 Type**
- 2 d₁**
- 3 d₂**
- 4 Length l**