



ROSTFREI
Inox
Stainless
Steel

Inch
sizes
available

3 Type

- E** with threaded blind bore
- C** with plain blind bore, Tol. H7

d₁	d₂			d₃ H7		d₄	h₁		h₂		h₃	t min.
	GN 6336.1	GN 6336.2	Thread (Type E)	Bushing steel	Bushing Stainless Steel		GN 6336.1	GN 6336.2	GN 6336.1	GN 6336.2		
32	M 6	-	M 6	B 6	-	12	21	20	10	10	8,5	12
40	M 6	M 8	M 8	B 6	B 8	14	26	26	13	13	10	14
50	M 8	M 10	M 10	B 8	B 10	18	34	32	17	17	10	18
63	M 10	M 12	M 12	B 10	B 12	20	42	40	21	21	14	22
80	M 12	M 16	M 16	B 16	-	25	52	52	25	27	15	30

Ausführung

- **GN 6336.1**
Plastic
Duroplast (PF)
black, shiny finish
Bushing
- Steel
zinc plated, blue passivated
- Stainless Steel AISI 303
- **GN 6336.2**
Plastic
Technopolymer (Polyamide PA)
- shock-resistant
- black, matt finish
Bushing
- Steel zinc
plated, blue passivated
- Stainless Steel AISI 303
- ISO-Fundamental tolerances → Page 1479
- Plastic characteristics → Page 1483
- RoHS compliant

Information

Star knobs GN 6336.1 / GN 6336.2 with protruding steel bushing have important advantages:

The face of the bushing is exactly square to the bore and is with the complete diameter out of steel or Stainless Steel. The protruding steel bushing allows a perfect cross-dowels connection.

see also...

- Star knobs GN 6336 (Cast iron / St. Steel / Aluminum) → Page 396
- Star knobs DIN 6336 (Plastic, without protruding bushing) → Page 398

How to order (Duroplast, bushing Stainless Steel)	1 d₁
	2 d₂ (d₃)
	3 Type
	4 Material bushing

GN 6336.1-50-M10-E-NI

How to order (Technopolymer, bushing steel)	1 d₁
	2 d₃ (d₂)
	3 Type

GN 6336.2-40-B8-C