



1 **Type**
TE Plastic Technopolymer (Polyamide PA)

2 d_1	3 d_2	4 Length $l \approx$								d_4	h_1	h_2	h_3
32	M 6	16 20 25 30 35 45 -								12	20	10	8,5
40	M 8	16 20 25 30 35 40 45 55								14	26	13	10
50	M 10	25 30 35 45 55 - -								18	32	17	10
63	M 12	30 35 40 50 60 - -								20	40	21	14

Specification

- Knob (Type ST) Technopolymer (Polyamide PA)
 - shock-resistant
 - black, matte finish
- **GN 6336.4** Threaded stud Steel zinc plated, blue passivated
- **GN 6336.5** Threaded stud Stainless Steel AISI 303
- *Plastic characteristics* → Page 1483
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Information

The star knobs have an immaculate contact or clamping surface thanks to the protruding steel / Stainless Steel bushing.

see also...

- *Star knobs 6336.4 (without protruding bushing, threaded stud steel) → Page 399*
- *Star knobs 6336.5 (without protruding bushing, threaded stud Stainless Steel) → Page 399*

How to order (Threaded stud steel)

1 **2** **3** **4**
GN 6336.4-TE-50-M10-30

1 Type
2 d_1
3 d_2
4 Length l

How to order (Threaded stud Stainless Steel)

1 **2** **3** **4**
GN 6336.5-TE-40-M8-16

1 Type
2 d_1
3 d_2
4 Length l