



ROSTFREI
Inox
Stainless
Steel

3 Type

- A without knurl
- B with knurl

| 1 d_1 | 2 d_2 | d_3 | h_1 | h_2 | t min. |
|----------------|----------------|-------|-------|-------|-------------|
| 21 | M 4 | 12,5 | 18 | 10,5 | 10 |
| 21 | M 5 | 12,5 | 18 | 10,5 | 10 |
| 25 | M 6 | 14,5 | 22,5 | 14 | 12 |
| 25 | M 8 | 14,5 | 22,5 | 14 | 12 |
| 31 | M 8 | 18,5 | 27 | 17 | 15 |
| 31 | M 10 | 18,5 | 27 | 17 | 17 |

Specification

- **GN 676.1**
Steel
blackened
- **GN 676.5**
Stainless Steel AISI 303
matte shot-blasted
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Information

Knobs GN 676.1 / GN 676.5 are used in applications where a push or pull movement is required. Their concave top gives a more comfortable thumb grip.

The knurled model (Type B) can be used as an attractively shaped knurled knob with a threaded blind hole.

see also...

- *Knurled knobs GN 676* → Page 62
- *Waist shaped knobs GN 75* → Page 59
- *Waist shaped Stainless Steel-Knobs GN 75.5* → Page 59

| | |
|--|----------------|
| How to order (Steel) GN676.1-21-M5-B | 1 d_1 |
| | 2 d_2 |
| | 3 Type |

| | |
|---|----------------|
| How to order (Stainless Steel) GN676.5-31-M10-A | 1 d_1 |
| | 2 d_2 |
| | 3 Type |