



3 Type

- A** with flange for surface mounting
- B** with female thread
- C** with male thread

1

2

| d | r | b | l ₁ ≈ | l ₂ | l ₃ min. | l ₄ |
|----|----|----|------------------|----------------|---------------------|----------------|
| 17 | 40 | 10 | 5,5 | 16,5 | 21,5 | 11 |
| 17 | 55 | 10 | 5,5 | 16,5 | 21,5 | 11 |

Specification

4

- Latch
Zinc die casting
plastic coated
black, RAL 9005, textured finish
red, RAL 3000, textured finish
- Indexing mechanism
- Type A
Zinc die casting / Plastic
- Type B / Type C
Steel / Plastic
Steel parts zinc plated, blue passivated
- Fastening flange
Zinc die casting
plastic coated
black, matte
- RoHS compliant



Information

Stop locks GN 702 are particularly suitable for light-weight applications not exposed to dynamic loads, e.g. for keeping drawers closed.

To mount stop locks of Type C, bore holes as shown in the diagram below must be set in the attachment surface.

These mounting holes are usually made by punching or with laser. For small series and steel sheets below 2 mm thickness, the sheet metal punches GN 123 are the tool of choice → Page 941.

The mounting bore holes can also be made by drilling / milling.

How to order

GN 702-17-40-C-SW

- 1** d
- 2** r
- 3** Type
- 4** Color