



3 Type

- A** Flat spindle tip
- B** Rounded spindle tip

d₁	Länge l			d₂	d₃	h	m	r
M 4	33	43	-	8	8	10	2,2	6
M 5	45	55	-	10	9	11	2,7	8
M 6	35	55	65	13	12	12	3,2	10
M 8	43	68	-	16	14	18	4	12
M 10	50	77	97	20	18	21	5	15
M 12	100	130	-	25	23	24	6	18

Specification

- Spindle
 - Steel **ST**
 - zinc plated, blue passivated
 - Stainless Steel AISI 304 **NI**
- Hexagon nuts ISO 4035
 - Steel
 - zinc plated, blue passivated
 - Stainless Steel AISI 304
- Pressure pad
 - Rubber, Neoprene (CR)
 - 85 Shore A ≈
 - vulcanized
 - black
- *Stainless Steel characteristics* → Page 1489
- *Elastomer characteristics* → Page 1483
- RoHS compliant



Information

- The two hexagon nuts are included parts of the order.
- see also...**
- *Clamp mounts GN 809 (for toggle clamps with solid clamping arm)*
→ Page 591
 - *Clamp mounts GN 801 (for toggle clamps with forked clamping arm)*
→ Page 590

How to order (Steel)

GN 708.1-M8-43-B-ST

- 1** d₁
- 2** Length l
- 3** Type
- 4** Material

How to order (Stainless Steel)

GN 708.1-M5-45-A-NI

- 1** d₁
- 2** Length l
- 3** Type
- 4** Material