



ELESA Original design M.643

1

2

Length l	d						a	b	h	t min.				
	Standard material (PP)	HT material (PA)								M4	M5	M6	M8	M10
86 ±0,5	M 5	M 6	-	-	M 6	-	14	23	44	-	10	12	-	-
94 ±0,5	M 5	M 6	-	-	-	-	14	24	48	-	10	12	-	-
117 ±0,5	M 4	M 5	M 6	M 8	M 6	M 8	15	25	49	10	10	12	13	-
120 ±0,5	M 5	M 6	M 8	-	-	-	15	25	49	-	10	12	13	-
132 ±0,5	M 5	M 6	M 8	-	-	-	16	26	54	-	10	12	13	-
150 ±1	M 6	M 8	M 10	-	-	-	16	27	56	-	-	12	13	17
179 ±1	M 8	M 10	-	-	M 8	-	16	27	57	-	-	-	13	17
235 ±1	M 8	M 10	-	-	-	-	18,5	29	61	-	-	-	13	17
300 ±1	M 10	-	-	-	-	-	22	32	64	-	-	-	-	17

**Specification**

- Plastic Technopolymer (Polypropylene PP)
  - shock-resistant
  - temperature resistant up to 100 °C
  - black, matt finish
- Plastic Technopolymer (Polyamide PA)
  - glass fibre reinforced
  - temperature resistant up to **200 °C**
  - black, matt finish
- Bushing Brass
- *Plastic characteristics* → Page 1141
- *Strength properties* → Page 1147
- **RoHS compliant**

3

**Information**

Cabinet „U“ handles GN 725 are known for their good design and the well proven elliptical profile. They meet the demand from an ergonomical angle.

see also...

- *Cabinet „U“ handles GN 565 (Aluminium)* → Page 60
- *Stainless Steel-Cabinet „U“ handles GN 565.5* → Page 63
- *Cabinet „U“ handles GN 625 (Plastic)* → Page 66

HT

Cabinet „U“ handle GN 725-179-M8	1	Length l
	2	d

Cabinet „U“ handle up to 200° C GN 725-86-M6-HT	1	Length l
	2	d
	3	Material