



- 2 Bore code**
B without keyway
K with keyway
Z with collet
- 4 Type**
A without handle
D with revolving handle
- 5 Coding**
S with standard scale
 0...90, 100 graduations
 acc. scale scheme
 d₁/100 A RA 0-10 20...90/10
 (only for bore code Z)

d ₁	d ₂ H8 Bore	d ₃	d ₄	d ₅	b -0,5	h	l ₁	l ₂	l ₃ ≈	r	Ø Handle
52	10	50	37	39,5	13	3,8	23	17	19	15,5	13
62	10	60	47	49,5	13	3,8	23	17	21	20,5	14

Specification

- Aluminum anodized, black
- Standard scale (coding **S**) engraved
- Cover
Plastic, light gray
- Collet / Hexagon nut
Brass
- Revolving cylindrical handles GN 599.5
 - Plastic, Technopolymer black, matte
 - Spindle
Stainless Steel AISI 303
- Keyway P9 DIN 6885 → Page 1420
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS compliant

Information

Control handwheels GN 736.1 are used for setting operations with low torque. Coarse setting is made by means of the cylindrical handle (fingertip grip) followed by fine setting using the knurled rim of the handwheel.

The model fitted with collet offers an absolutely reliable mounting on the shaft and at the same time allows an easy setting of the adjustable scale ring wheel. The scale is wear resistant and easily legible since the engraved alu colored numbers contrast with the black anodized surface. Besides the standard scale (Coding S) the control handwheels can be supplied with any type of graduation. For full details of the available graduations, numbering sequence, number position and type of scale, see page 252.

see also...

- Countersunk washers GN 184 (for axial fixing) → Page 814
- Clamping elements GN 826 (for adjustable spindles) → Page 268

How to order (without scale)	1 d ₁
	2 Bore code
	3 d ₂
	4 Type

How to order (with scale)	1 d ₁
	2 Bore code
	3 d ₂
	4 Type
	5 Coding