



3 Type

- D** with plain shaft
- E** with threaded shaft

2

d ₁	d ₂ h8 Type D		d ₃ Type E		d ₄ h13	l ₁ ≈	l ₂	l ₃	A/F Internal hexagon
	ST / AL	KT	ST / AL	KT					
16	7	7	M 6	M 6	10	49	11	5,5	3
20	8	8	M 8	M 8	13	61	13	6	4
25	10	10	M 10	M 10	16	75	14	8	5
32	13	13	M 12	M 12	20	95	21	10,5	6
36	16	-	M 16	-	22	106	26	11	8

Specification

- Steel **ST**
zinc plated, blue passivated
- Aluminum **AL**
glossy finish
- Plastic **KT**
Technopolymer (Polyamide PA)
- temperature resistant up to 110 °C
- black, matte finish
- Spindle steel
zinc plated, blue passivated
- *ISO-Fundamental tolerances* → Page 1479
- *Plastic characteristics* → Page 1483
- *RoHS-compliant (only material ST, KT)*

1

Information

Revolving handles DIN 98 type D are supplied unassembled so that the shaft can be press fitted or screwed into a tapped blind bore prior to assembly.

During mounting, easy blows with a soft hammer are sufficient to drive the handle into place.

How to order

DIN 98-KT-32-D

- 1** Material
- 2** d₁
- 3** Type