



ELESA Original design NIL.R

<sup>1</sup> s <sub>1</sub>	<sup>2</sup> s <sub>2</sub>	w	l <sub>1</sub>	l <sub>2</sub>
R 20	10	0,8 ... 2	3	12
R 20	15	1 ... 2	5	11,5
R 25	10	0,8 ... 2	3	11,5
R 25	15	1 ... 2,5	5	11,5
R 25	20	1 ... 3	5	11,5
R 30	10	1 ... 2	5	11,5
R 30	15	1 ... 2,5	5	11,5
R 30	20	1 ... 3	5	11,5
R 35	20	1 ... 2,5	5	11,5
R 35	25	1 ... 3	5	11,5
R 40	15	1 ... 2	5	12
R 40	20	1 ... 3	5	12
R 40	25	1 ... 3	5	11,5
R 40	30	1 ... 3	5	11
R 45	15	1,5 ... 2	5	11
R 45	20	1 ... 3	5	11,5
R 45	25	1 ... 3	5	12
R 50	20	1 ... 3	5	15

<sup>1</sup> s <sub>1</sub>	<sup>2</sup> s <sub>2</sub>	w	l <sub>1</sub>	l <sub>2</sub>
R 50	25	1 ... 3	5	11,5
R 50	30	1 ... 3	5	12
R 50	35	1 ... 3,5	5	14,5
R 50	40	1,5 ... 3	5	15
R 60	20	1 ... 3	5	14,5
R 60	30	1 ... 2,5	5	15
R 60	40	1 ... 3	5	14
R 60	50	1,5 ... 3,5	5	14,5
R 70	30	1 ... 3	5	15
R 70	40	1,5 ... 3	5	20
R 80	20	1 ... 3	5	18
R 80	30	1 ... 2,5	5	14,5
R 80	40	1 ... 3	5	14,5
R 80	50	1,5 ... 4	5	22
R 80	60	1,5 ... 3,5	5	25
R 100	40	1,5 ... 4	5	14,5
R 100	50	1,5 ... 4,5	5	24

**Specification**

- Plastic Technopolymer (Polyethylen PE)
  - black, RAL 9005, matt ● SW
  - grey, RAL 7040, matt ● GR
- Plastic characteristics → Page 1489
- RoHS compliant

**On request**

- other sizes
- white (WS)

**Information**

Tube end plugs GN 991 have been designed for sealing tube ends for safety or optical reasons.

They are pressed into the tube end either by hand or with a mallet.

see also...

- Insert bushings GN 992 (Aluminum, with female thread) → Page 1059

**How to order**

**GN 991-R25-20-SW**

<sup>1</sup>	s <sub>1</sub>
<sup>2</sup>	s <sub>2</sub>
<sup>3</sup>	Color